

PRODUCT INFORMATION
CONTROL ADDITIVE

ADDI-PROX SC/F

is a water-miscible system cleaner. Oil residues, sediments, bacteria, fungi, or any other dirt will be removed from the machine, if cleaned with ADDI-PROX SC/F before a new filling with water-miscible cutting fluids. This ensures optimal conditions for the cutting fluid.

BENEFITS

- Disinfection of the circulation system
- Cleans out all kinds of residues
- Compatible with all cutting fluid systems (stand-alone machines or central system)
- Is to be removed together with the old cutting fluid
- Good material compatibility
- Clean machines thanks to high washing, flushing, and cleaning power
- Easy-to-use

DATA OF PRODUCT | CONCENTRATE

DETERMINATION	METHOD	UNIT	VALUE
Density, 20°C	DIN 51 757	[kg/m ³]	1054
Kin. viscosity, 40°C	DIN EN 16 896	[mm ² /s]	2
Refractive index, n _D ²⁰	DIN 51 423	---	1.375

RECOMMENDED CONCENTRATION (DEPENDING ON APPLICATION AND CONDITIONS)

- Standard concentration at room temperature: 1.0 - 2.0%
- Product can be use in a higher concentration. Please contact your coolant partner for more information.
- Recommended duration of action in circulation: at least 8h.
- Processing can be continued if personal protective equipment is worn.
- Use biocides safely. Before use, always read the characterisation and the product information.
- See also "Technical information: New fill general".

SHELF LIFE | OPERATING AND STORAGE CONDITIONS

6 months under ambient storage conditions.

INDUSTRIAL HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION

For more details about health and safety please read the information on the safety data sheet.

DISPOSAL

In compliance with the local waste regulations.